CI/SfB		
	Yw7	
CAW P22		
Uniclass L69:P99		

Description

AT115 is ideal for cleaning and degreasing sensitive surfaces such as plastics, painted and powder-coated components as well as metals. Can also be used for cleaning tools and equipment.

Packaging

1 litre tin (10 per box)

Colour

Transparent

Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Application

- Apply by cloth part soaked in AT115.
- Flash-off time is approximately 5 minutes.
- A trial test to ensure there is no leaching/migration is recommended. Examples of where this is necessary are PVC with a high plasticiser content, tar, bitumen and organic elastomers.
- Always refer to the sealant data sheet for full application instructions.

Storage

Store in dry shaded conditions between +5°C and +25°C.

Shelf Life

24 months when stored as recommended in original unopened packaging.

Health & Safety Precautions

Safety data sheet must be read and understood before use. Highly flammable- keep away from open flames and other ignition sources.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.





AT115

Cleaner for Plastics

Usage / Purpose

AT115 is used to remove grease, oil, etc.

Key Benefits

- Rapid drying and easy to use
- Ideal for cleaning sensitive substrates prior to the application of illbruck sealants



Construction Products Group

Tremco CPG UK Limited Coupland Road Hindley Green, Wlgan WN2 4HT United Kingdom T: +44 1942 251400 F: +44 1942 251410

2020/12

info.uk@cpg-europe.com www.cpg-europe.com