

SINIDEX EXTREME



- Maximum vent width of 950mm and a maximum weight of 35 Kgs.
- All sash fixings to pick up reinforcement when using HS60 16 Extreme.
- Opening angle of 87° with the HS90 12 Extreme and 60° with the HS60 16 Extreme.
- Available in 13mm and 17mm stack heights.
- Cycle tested with normal operation after 25,000 cycles.
- Easy to fit with adjustable friction mechanism.
- Overlap slide for enhanced smooth operation.
- 2 reinforced Heavy Duty links for added strength.
- Easy clean complies with BS8213.
- Manufactured using high grade Austenitic 304 stainless steel to BSEN 10088-2 and Ferritic 430 stainless steel for enhanced corrosion resistance.
- BBA tested in accordance with BS6375-2:1987, BS6375-2:2009 and BSEN13126-6:2008

MAXIMUM WINDOW WEIGHTS & REBATE SIZES						
PRODUCT	SIZE INS	SIZE MM	MAX. VENT WIDTH MM	MAX. VENT WEIGHT KG	STACK HEIGHT MM	OPENING ANGLE
HS90 12 Extreme	12	311	750	30	13/14 & 16/17	87
HS60 16 Extreme	16	406	950	35	13/14 & 16/17	60

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEETS THE REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS
 Cotswold Architectural Products Ltd, Manor Park Industrial Estate, Manor Park Road, Cheltenham, Gloucestershire, GL51 9SQ
 Tel +44 (0) 1242 233993, Email: info@cotswoldap.com, Web: www.cotswoldap.com